



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH6025S	Sleeve	B	12	6.0	0.14	4000	19.25	0.545	4.21	27.20	•	•	•	•	•	62	100	7.2
RDM6025S				6.0	0.10	3000	14.10	0.399	2.42	22.71	•	•	•	•	•			
RDL6025S				6.0	0.07	2500	11.83	0.335	1.74	20.16	•	•	•	•	•			
RDH6025B	Ball			6.0	0.14	4000	19.25	0.545	4.21	27.20	•	•	•	•	•			
RDM6025B				6.0	0.10	3000	14.10	0.399	2.42	22.71	•	•	•	•	•			
RDL6025B				6.0	0.07	2500	11.83	0.335	1.74	20.16	•	•	•	•	•			
RDH6025S2	Sleeve	24	12.0	0.14	4000	19.25	0.545	4.21	27.20	•	•	•	•	•				
RDM6025S2			12.0	0.10	3000	14.10	0.399	2.42	22.71	•	•	•	•	•				
RDL6025S2			12.0	0.09	2500	11.83	0.335	1.74	20.16	•	•	•	•	•				
RDH6025B2	Ball		12.0	0.14	4000	19.25	0.545	4.21	27.20	•	•	•	•	•				
RDM6025B2			12.0	0.10	3000	14.10	0.399	2.42	22.71	•	•	•	•	•				
RDL6025B2			12.0	0.09	2500	11.83	0.335	1.74	20.16	•	•	•	•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA	VDE
12V	•	•	•	•	•	
24V	•	•	•	•		•

